

SCTE • ISBE[®]

S T A N D A R D S

Network Operations Subcommittee

AMERICAN NATIONAL STANDARD

ANSI/SCTE 38-7 2017

**Hybrid Fiber/Coax Outside Plant Status Monitoring
SCTE-HMS-Transponder Interface Bus (TIB)-MIB
Management Information Base (MIB) Definition**

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) / International Society of Broadband Experts (ISBE) Standards and Operational Practices (hereafter called “documents”) are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability, best practices and ultimately the long-term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE•ISBE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE•ISBE members.

SCTE•ISBE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents, and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

Attention is called to the possibility that implementation of this document may require the use of subject matter covered by patent rights. By publication of this document, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE•ISBE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE•ISBE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2017
140 Philips Road
Exton, PA 19341

Contents

| | |
|---------------------------------|----------|
| 1. SCOPE | 4 |
| 2. COPYRIGHT | 4 |
| 3. NORMATIVE REFERENCE | 4 |
| 4. INFORMATIVE REFERENCE | 4 |
| 5. TERMS AND DEFINITIONS | 4 |
| 6. REQUIREMENTS | 4 |

1. Scope

This document is identical to SCTE 38-7 2008 except for informative components which may have been updated such as the title page, NOTICE text, headers and footers. No normative changes have been made to this document.

This document contains information about the communications state of devices connected to the transponder, as well as indicating what device-specific MIB each device supports. These devices are typically connected to the transponder via a serial communications link (bus).

2. Copyright

The MIB definition found in this document may be incorporated directly in products without further permission from the copyright owner, SCTE.

3. Normative Reference

| | |
|--|--|
| ANSI/SCTE 25-3 2005 | Hybrid Fiber Coax Outside Plant Status Monitoring – Power Supply to Transponder Interface Bus (PSTIB) Specification v1.1 |
| ANSI/SCTE 36 2007 (formerly HMS 028) | SCTE-ROOT Management Information Base (MIB) Definitions |
| ANSI/SCTE 37 2008 (formerly HMS 072) | Hybrid Fiber/Coax Outside Plant Status Monitoring SCTE-HMS-ROOTS Management Information Base (MIB) Definition |
| ANSI/SCTE 38-1 2004 (formerly HMS 026) | Hybrid Fiber/Coax Outside Plant Status Monitoring SCTE-HMS-PROPERTY-MIB Management Information Base (MIB) Definition |
| ANSI/SCTE 38-3 2008 (formerly HMS 024) | Hybrid Fiber/Coax Outside Plant Status Monitoring SCTE-HMS-COMMON-MIB Management Information Base (MIB) Definition |
| IETF RFC 1155 | Structure and Identification of Management Information for TCP/IP-based Internets [RFC1155-SMI] |
| IETF RFC 1157 | A Simple Network Management Protocol (SNMP) [RFC1157-SNMP] |
| IETF RFC 1212 | Concise MIB Definitions for SNMPv1 |
| IETF RFC 1213 | MIB for Network Management of TCP/IP-based internets: MIB-II [RFC1213-MIB] for SNMPv1 |
| IETF RFC 1215 | A Convention for Defining Traps for use with the SNMP for SNMPv1 |

4. Informative Reference

None

5. Terms and Definitions

This document defines the following terms:

Management Information Base (MIB) - the specification of information in a manner that allows standard access through a network management protocol.

6. Requirements

This section defines the mandatory syntax of the SCTE-HMS-TIB-MIB MIB. It follows the IETF Simple Network Management Protocol (SNMP) for defining the managed objects.

The syntax is given below.

```
-- *****
-- *
-- * Module Name: HMS050R5.MIB (SCTE 38-7)
-- *
-- * SCTE Status: ADOPTED JANUARY 11, 2002
-- *
-- * This MIB contains information about the communications state of
-- * devices connected to the transponder, as well as indicating what
-- * device-specific MIB each device supports. These devices are typically
-- * connected to the transponder via a serial communications link (bus).
-- *
-- *****
```

SCTE-HMS-TIB-MIB DEFINITIONS ::= BEGIN

IMPORTS

```
OBJECT-TYPE
FROM RFC-1212
transponderInterfaceBusIdent
FROM SCTE-HMS-ROOTS
;
```

tibAttachedDevices OBJECT-TYPE

```
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
```

"Bit Map that indicates addresses of attached devices. Bit set means a device using that address is attached to NE.

| Bits | Addresses |
|------|-----------|
| 0 | Not used |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 4 | 4 |
| 5 | 5 |
| 6 | 6 |
| 7 | 7 |
| 8 | 8 |
| 9 | 9 |
| 10 | 10 |
| 11 | 11 |
| 12 | 12 |
| 13 | 13 |
| 14 | 14 |
| 15 | 15 |
| 16 | 16 |
| 17 | 17 |
| 18 | 18 |
| 19 | 19 |
| 20 | 20 |
| 21 | 21 |
| 22 | 22 |
| 23 | 23 |
| 24 | 24 |

```

25 25
26 26
27 27
28 28
29 29
30 30
31 31
"

```

```
::= { transponderInterfaceBusIdent 1 }
```

tibCommStatus OBJECT-TYPE

SYNTAX INTEGER

ACCESS read-only

STATUS mandatory

DESCRIPTION

"Bit Map that indicates attached devices that are not communicating. Bit set means a device using that address is not communicating. This only applies to addresses whose bit is set in tibAttachedDevices.

| Bits | Addresses |
|------|-----------|
| 0 | Not used |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 4 | 4 |
| 5 | 5 |
| 6 | 6 |
| 7 | 7 |
| 8 | 8 |
| 9 | 9 |
| 10 | 10 |
| 11 | 11 |
| 12 | 12 |
| 13 | 13 |
| 14 | 14 |
| 15 | 15 |
| 16 | 16 |
| 17 | 17 |
| 18 | 18 |
| 19 | 19 |
| 20 | 20 |
| 21 | 21 |
| 22 | 22 |
| 23 | 23 |
| 24 | 24 |
| 25 | 25 |
| 26 | 26 |
| 27 | 27 |
| 28 | 28 |
| 29 | 29 |
| 30 | 30 |
| 31 | 31 |
| " | |

```
::= { transponderInterfaceBusIdent 2 }
```

tibDevicesAddressedTable OBJECT-TYPE

SYNTAX SEQUENCE OF TibDevicesAddressedEntry

ACCESS not-accessible
 STATUS mandatory
 DESCRIPTION
 "Table containing identity of devices addressed by this NE.
 This table should contain entries ONLY for devices that are physically
 connected to the NE. If a device is not connected, no entry should be
 created in the table for that address/index."
 ::= { transponderInterfaceBusIdent 3 }

tibDevicesAddressedEntry OBJECT-TYPE
 SYNTAX TibDevicesAddressedEntry
 ACCESS not-accessible
 STATUS mandatory
 DESCRIPTION
 "Entry containing information about individual devices"
 INDEX { tibDeviceAddress }
 ::= { tibDevicesAddressedTable 1 }

TibDevicesAddressedEntry ::=

```
SEQUENCE
{
  tibDeviceAddress
    INTEGER,
  tibDeviceIdentity
    OBJECT IDENTIFIER,
  tibControlMode
    INTEGER
}
```

tibDeviceAddress OBJECT-TYPE
 SYNTAX INTEGER (1..31)
 ACCESS read-only
 STATUS mandatory
 DESCRIPTION
 "Index into tibDevicesAddressedTable."
 ::= { tibDevicesAddressedEntry 1 }

tibDeviceIdentity OBJECT-TYPE
 SYNTAX OBJECT IDENTIFIER
 ACCESS read-only
 STATUS mandatory
 DESCRIPTION
 "Device identification. root OID for MIB that this device supports.
 For Power Supply use psIdent from SCTE-HMS-ROOTS (1.3.6.1.4.1.5591.1.4)
 For Fiber Node use fnIdent from SCTE-HMS-ROOTS (1.3.6.1.4.1.5591.1.5)
 For Generator use genIdent from SCTE-HMS-ROOTS (1.3.6.1.4.1.5591.1.6)"
 ::= { tibDevicesAddressedEntry 2 }

tibControlMode OBJECT-TYPE
 SYNTAX INTEGER { remote(1), local(2), notCommunicating(3) }
 ACCESS read-only
 STATUS optional
 DESCRIPTION
 "Control mode for this device"

- 1 = Remote device will respond to commands from master NE
- 2 = Local device is under local control and will not respond to commands from master NE
- 3 = This device is not responding.

This item requires entries in the discrete property table"

::= { tibDevicesAddressedEntry 3 }

END